



BASIC PARAMETERS

Model	Nominal Voltage	Rated Capacity	Max Discharge Current	Dimension
KETLF1206	12.8V	6Ah	6A	151*65*95mm
KETLF1210	12.8V	10Ah	10A	150*95*95mm
KETLF1220	12.8V	20Ah	20A	181*76*165mm
KETLF1230	12.8V	30Ah	30A	194*132*170mm
KETLF1240	12.8V	40Ah	40A	198*166*170mm
KETLF1250	12.8V	50Ah	50A	198*166*170mm
KETLF1260	12.8V	60Ah	60A	229*138*208mm
KETLF1280	12.8V	80Ah	80A	260*168*209mm
KETLF12100	12.8V	100Ah	100A	329*172*214mm
KETLF12150	12.8V	150Ah	150A	483*170*240mm
KETLF12200	12.8V	200Ah	200A	522*240*218mm
KETLF12300	12.8V	300Ah	200A	520*269*220mm
KETLF12400	12.8V	400Ah	250A	520*269*220mm
KETLF2440	25.6V	20Ah	20A	198*166*170mm
KETLF2440	25.6V	40Ah	40A	260*168*209mm
KETLF2460	25.6V	60Ah	60A	329*172*214mm
KETLF24100	25.6V	100Ah	100A	522*240*218mm
KETLF24200	25.6V	200Ah	200A	520*269*220mm



BASIC PARAMETERS

Model	Volatage (V)	Capacity (mAh)	Dimensions(+/-1mm)		
			Length	Width	Height
KET-LI1S1P	3.7V	2600	18.5±1	18.5±1	66±1
KET-LI2S1P	7.4V	2200	37±1	18.5±1	66±1
KET-LI2S1P	7.4V	2200	18.5±1	18.5±1	130±1
KET-LI2S1P	7.4V	3200	26.5±1	26.5±1	100±1
KET-LI2S1P	7.4V	2500	18.5±1	18.5±1	130±1
KET-LI3S1P	10.8V	2200	55.5±1	18.5±1	66±1
KET-LI3S1P (Triangle)	11.1V	2000	37±1	37±1	66±1
KET-LI3S1P	10.8V	2250	55.5±1	18.5±1	66±1
KET-LI4S1P	14.4V	2200	37±1	18.5±1	66±1
KET-LI4S1P	14.4V	2200	37±1	37±1	66±1
KET-LI4S1P (Triangle)	22.2V	2000	37±1	37±1	130±1